




HOSHIZAKI

















	ITEM	Hoshizaki Undercounter Freezer					
	MODEL	FT-156MA-S					
◬	POWER SUPPLY	1 Phase 230V 50Hz Capacity: 0.9kVA (4.08A)					
	AMPERAGE	Rated 2.6A					
A	ELECTRIC CONSUMPTION	Motor 415W Heater 375W					
		Refrigeration 349W Defrost 330W *W					
	HEAT REJECTION						
	POWER CORD	2.0m (UK Plug with Earth Wire)					
	EFFECTIVE CAPACITY	318L					
	OUTSIDE DIMENSIONS	1500mm (W) x 600mm (D) x 850(-880) mm (H)					
	INSIDE DIMENSIONS	1140mm (W) x 436mm (D) x 599mm (H)					
	EXTERIOR	Stainless Steel, Galvanized Steel (Rear/Bottom) ABS Plastic (Top & Bottom on Door)					
	INTERIOR	Stainless Steel, ABS Plastic (Door)					
	INSULATION	Polyurethane Foam					
	INSULATION FOAM BLOWING AGENT	Cyclopentane					
	REFRIGERATION SYSTEM	Forced Air Circulation					
	DEFROST SYSTEM	Glass Tube Heater					
	COMPRESSOR	Hermetic					
	CONDENSER	Fin and Tube type, Air—cooled					
	EVAPORATOR	Fin and Tube Type					
	REFRIGERANT	R404A					
	TEMPERATURE CONTROL	Microprocessor controlled Adjustable from -23 to -7°C					
	DEFROST CONTROL	Microprocessor controlled					
-	ELECTRIC CIRCUIT PROTECTION	Fuse, Earth Wire					
	COMPRESSOR PROTECTION	Motor Protector					
	LEG	Plastic Adjustable 150 to 180mm					
	SHELF	4pcs.					
	WEIGHT	Net: 81kg (Gross: Approx. 86kg)					
	PACKAGE	Carton 1565mm (W) x 680mm (D) x 790mm (H)					
	ACCESSORIES	_					
◬	OPERATING CONDITIONS	Ambient Temperature: 5—38°C Voltage Range: Rated Voltage±6%					
	*We reserve the right t	o make changes in specifications and design without prior notice.					

- 1. Install the product properly in accordance with the instructions on location, electrical connections stated in the instruction manual provided. Allow 10mm extra space at the installation site to meet any installation requirements (additional spacing is also required for proper air flow and pipe connections).
- 2. The heat rejection is based on the reached pulldown temperature at ambient temperature of 35°C and power supply of 230V 50Hz.

 The amperage and electric consumption are based on measurements at ambient temperature of 38°C and power supply of 230V 50Hz.

 3. The cabinet temperature range of -23 to -7°C is guaranteed at ambient temperature of 35°C.

 4. Product code: T273-C100 (HS)

APPROVED KAWAKAMI			ECKED ANG	DESIGNED LIANG	DRAWN ZHANG		SCALE 1	/20	TRIGON	OMETRY
LIUYIB0	W)	X	₹	2021.03.09 DATE		DATE 2019.03.15		DRAWING NO. D24606		SYMBOL
APPROVED	DESIG	NED	SYMBOL							<u> </u>